

### Heavy Lift

### PCM Moineau™ 8E2700

Performance	SI	US
Nominal displacement	0.08 m <sup>3</sup> /d/rpm	0.50 bpd/rpm
Pressure rating	270 bars / 27000 kPa	3900 psi
Pressure per cavity	4.7 bars / 470 kPa	70 psi
Number of engaged cavities	57	
Minimum/maximum speed	50/500 rpm, depending on application	
ISO 15136-1 compliance	V3/Q3 - Higher grade upon request	
Helix angle	22.1°	
Cavity flow area	741 mm <sup>2</sup>	1.15 in <sup>2</sup>




Stator Specifications	Standard		Flush	
	SI	US	SI	US
Top connection (API nominal size)	3½" (88.9 mm) EUE Box		2⅞" (73.0 mm) EUE Box	
Bottom connection (API nominal size)	3½" (88.9 mm) EUE Pin		2⅞" (73.0 mm) EUE Pin	
Body outside diameter	95.3 mm	3.75"	93.2 mm	3.67"
Maximum outside diameter	114.3 mm	4.50"	93.2 mm	3.67"
Maximum outside diameter if special clearance couplings are used	106.2 mm	4.18"	93.2 mm	3.67"
Length	4.49 m	14' 8.9"	6.54 m	21' 5.6"
Weight	62 kg	136 lb	81 kg	178 lb
Number of elements	1.5		1.5	
Top bushing or tag bar	Available		Available	
Notes	Includes 6.0 ft pup joint			

Rotor Specifications	SI	US
Top connection (nominal size)	⅞" (22.2 mm) API Pin	
Total length	4.75 m	15' 7.0"
Helix length	4.54 m	14' 10.7"
Weight	41 kg	90 lb
Minor diameter	42.1 mm	1.657"
Major diameter	50.9 mm	2.004"
Head diameter	44.0 mm	1.732"
Maximum OD with full size coupling	50.9 mm	2.004"
Maximum OD with slimhole coupling	50.9 mm	2.004"
Orbit diameter with full size coupling	59.7 mm	2.350"
Orbit diameter with slimhole coupling	59.7 mm	2.350"
Coating type	Chromium	
Coating thickness	Information upon request	
This pump is available as (optional):	<b>PCM Slugger</b>	
This pump is available with (optional):	Paddle rotor	



Completion Considerations
<i>Stator maximum OD must be less than casing drift diameter (some extra clearance is recommended)</i>
<i>Rotor maximum OD must be less than tubing drift diameter</i>
<i>Rotor orbit diameter must be less than pup joint drift diameter</i>

Contact your PCM representative for an operator's manual  
 Top and bottom stator connections can be customized as required (pin/pin, box/box, etc., or changes in size in some cases)  
 With a paddle rotor, the rotor length is extended by 600 mm (2 ft). Contact PCM for further details.  
 This is not a contractual document. PCM reserves the right to make changes at any time.



The flow rate chart is calculated using the validated displacement for this pump.

Revision Number 2-1-1 (2022/01/19)