


PCM DRIVER™ CD-60

THE SURFACE DRIVE SOLUTION FOR YOUR
PCP OPERATIONS

keep it moving 



CD-60

Designed with the latest technology to ensure full compliance with Oil and Gas standards, PCM Driver™ driveheads are safe and reliable surface drive solutions specifically engineered for long life in all your PCP operations.

The design and qualification of PCM Driver™ driveheads comply with ISO 15136-2 Surface Drive System requirements.

The **PCM Driver™ CD-60** is a cost-effective full life cycle solution to perform with all your power requirements up to **60 HP**.

The CD-60 is available with your choice of two different thrust bearings, standard and Heavy Duty (HD), to meet your application requirements.

» BENEFITS

- Fully internal brake system
- Patented environmental **PCM EcoSeal Stuffing Box**
- Rotating parts fully covered
- Low maintenance requirements
- Associated service and technical support



PCM

Artificial Lift Solutions

SAFETY

Belt guard:

- Compact and durable, all rotating parts fully protected

Fully internal brake system:

- Efficient backspin control

Anti-ejection system available for polished rod clamp.

ATEX certification is available.

LOW MAINTENANCE REQUIREMENT

Only maintenance required is regular visual inspection, seal greasing, and oil changes.

PCM EcoSeal Stuffing Box – Patented environmental integral rotating sealing system

- Redundant seals
- No seepage
- Long life

FIRST CLASS SERVICE

- PCM service team available worldwide to support customer
- Dedicated PCP team will support customer regarding any queries or issues faced with our PCM Driver™.

SPECIFICATIONS

Drive mode	Belt and pulleys driven
Max. driven sheave	31.5" (800 mm)
Ambient conditions	-40°F to 105°F (-40°C to +40°C)
Braking system	Compact integral hydraulic gear pump
Max. speed	500 RPM
Max torque	1 200 ft. lb (or 1 627 N.m)
Sealing system	PCM EcoSeal Stuffing Box
Max. produced fluid temperature	390°F (200°C)
Max. produced fluid pressure	Dynamic: 1 000 PSI (70 Bar) Static: 1 000 PSI (70 Bar)
Shaft type	Hollow shaft
PR diameter	1"1/4 (31.75 mm) or 1"1/2 (38.10 mm)
API wellhead	Flanged 3"1/8 3M R31 or 4"1/16 3M R37
Bearing dynamic axial load rating (Ca, ISO 281)	CD-60 : 161 862 lb (720 kN) CD-60 (HD) : 238 000 lb (1060 kN)
Bearing dynamic axial load rating (Ca90)	CD-60 : 42 000 lb (187 kN) CD-60 (HD) : 61 800 lb (275 kN)
Bearing load for L10 life of 25 000 hours at 500 RPM	CD-60 : 10.1 T CD-60 (HD) : 14.8 T
Prime mover	Electric motor NEMA or IEC
Max. motor HP	60 HP (45 kW)
Max. noise level	< 70 dB
Total weight	720 lb (327 kg)
Dimensions	60.7" x 33.1" x 43.9" (1.54 x 0.84 x 1.12 m)

For further information, please contact your PCM local representative:

www.pcmals.com